

### PRODUCT CODE

## **ESCORT PASSPORT 9500i**

### **PRODUCT DESCRIPTION**

GPS equipped portable radar safety detector

# **ESCORT**

### NARRATIVE

The Passport 9500i provides the latest in GPS powered filtering with Truelock<sup>™</sup>. A radar frequency filtering system, that permanently eliminates false alerts by location and frequency. The Passport 9500i provides total coverage with X, K, Superwide Ka, International Ku and Safety Warning System (SWS) radar capability, combined with front and rear laser detection. The Passport 9500i also introduces intuitive AutoSensitivity<sup>™</sup> which increases the range as your speed increases.

### **FEATURES**

10 x Range vs. Imports	Easy-to-Use Options and Controls
All Radar and Laser Band Coverage	Digital Signal Processing (DSP) Virtually
	Eliminates False Alerts
Multi-Sensor Laser Protection	Ultra-Bright High Definition Display
NEW Truelock <sup>™</sup> Technology	Brightness Control with Dark Mode
Advanced AutoSensitivity <sup>™</sup>	One year limited warranty
9 Selectable Features	Dimensions: 3.6 x 7.4 x 13.6cm

#### **SPECIFICATIONS**

Operating Bands:	Power Requirement:	
• X-band: 10.525 GHz ± 25 MHz	<ul> <li>12VDC, Negative Ground</li> </ul>	
<ul> <li>K-band: 24.150 GHz ± 100 MHz</li> </ul>	<ul> <li>Coiled SmartPlug<sup>™</sup> with Mute Button</li> </ul>	
<ul> <li>Ka-band: 34.700 GHz ± 1300 MHz</li> </ul>		
• Ku-band: 13,400 GHz ± 25 MHz		
Laser: 904nm, 33MHz bandwidth		
Radar Receiver/Detector Type:	Programmable Features:	
<ul> <li>Superheterodyne, Varactor-Tuned VCO</li> </ul>	Power-On Indication	
<ul> <li>Scanning Frequency Discriminator</li> </ul>	Speed Alert	
Digital Signal Processing (DSP)	Power-On Sequence	
g	Signal Strength Meter	
	• AutoMute™	
	Auto Volume	
	• Units	
	Voice	
	• Bands	
GPS Receiver:	Sensitivity Control:	
SiFRstar III	• Highway	
	Auto Sensitivity	
	• City	
Laser Detection:	Additional Patented Technology:	
Ouantum Limited Video Receiver	Auto Calibration Circuitry	
Multiple Laser Sensors	Smartshield VG2 Immunity	
• Multiple Laser Sensors	• Smartshield VG2 minumity	
Display Type:		
• 280 LED Alphanumeric		
<ul> <li>Bar Graph, Speed Alert, Expert Meter™,</li> </ul>		
Spec Display™		
• 5 levels of brightness control including full Dark		
• 5 levels of brightness control including full Dark		