



**PRODUCT CODE: FM FMLITE**

**BARCODE: 9332820006285**

### **PRODUCT DESCRIPTION**

GSM + GPS Vehicle and Asset Locator and Tracking System

### **FEATURES**

- The Fleetminder FM Lite is a reliable live GPS tracking system.
- Simple to use and install requiring just three wires.
- The Fleetminder FM Lite is easily programmed for specific requirements and any changes or updates can be done over the air by SMS
- Can track and locate an asset or vehicle via SMS without web tracking subscription.
- The compact size of this unit (83mm x 74mm x 22mm) means the fleetminder FM can be mounted anywhere.
- Standard 3 minute reporting with 1 minute upgrade option.

### **BENEFITS**

- Monitor staff and vehicles 24/7.
- Real time WEB based management tool.
- Reports on inefficient staff and assets.
- Improves customer service by reducing response times.
- Reduce mileage and vehicle abuse.
- Safeguard your staff and assets.
- Reduce insurance premiums.
- Report by SMS or Web.
- Integrate to an existing alarm.
- Ability to remotely lock/unlock doors, disable the starter motor or sound the alarm.
- 24/12V compatible
- In-built backup battery

### **APPLICATIONS**

- Vehicle security and monitoring.
- Service industry – staff security and location.
- Tradesman – staff security and location.
- Delivery and pickup – staff security, location & routing
- Fleet management – staff security and location.
- Track stolen or lost vehicles.
- Sales personnel – staff security, location & customer visits.

### **OPTIONS**

- Harsh Braking, Harsh Acceleration and Crash Sensor
- Fuel Level sensor

## FEATURES:

<b>SMS:</b> Reporting of vehicle location, speed and direction sent direct to users' mobile phone via SMS, or to a PC via GPRS	<b>GPRS:</b> Live tracking with Fleetminder tracking software.
<b>Reports:</b> Useful management reports including: Vehicle Activity Report, Vehicle Site Report, Vehicle Mileage Report, Vehicle Stop Report, Vehicle Trip Report, Vehicle Over-Speed Report and Vehicle Idle Report.	<b>External GPS &amp; GSM Antennas:</b> Improves GPS & GSM reception.
<b>2 x inputs:</b> Typically used for interfacing automotive security systems. However it can be configured for other purposes such as accessories, door open or other switch modes.	<b>2 x outputs:</b> for controlling external relays such as lock/unlock doors, disable starter motor or sound the siren etc.
<b>Map Views:</b> <ul style="list-style-type: none"> <li>■ Hi-res aerial and satellite imagery. Easy to read dynamic maps.Simple drag, pan &amp; zoom controls.</li> <li>■ Intuitive user experience.Unrivalled map detail.</li> <li>■ Two way GPRS messaging for main functions.</li> <li>■ 2D, 3D, Birds Eye View and the latest Street View through Virtual Earth and Google Maps.</li> <li>■ Reverse Geocoding showing address.</li> </ul>	<b>Live Tracking Secure Log-in Page:</b> Secure and reliable. Fleetminder live tracking system allows you to use WEB browser to monitor your vehicles. Each user is supplied with their own unique username & password. The Fleetminder live tracking system allows you to monitor more than one vehicle or asset at one time.
<b>Easy Online Track Features:</b> Automatically resizes to display all vehicles. Replay a day activity for single/multiple vehicles. Draw Geofences directly onto the map. Multiple reports (Activity, Idle, Overspeed, Mileage, etc.)	<ul style="list-style-type: none"> <li>• SOS Panic Button</li> <li>• One year limited warranty</li> </ul>

## HARDWARE SPECIFICATIONS:

<b>GPS</b> <ul style="list-style-type: none"> <li>• <b>Channels:</b> 20 parallel tracking</li> <li>• <b>Correlators:</b> 200,000 plus</li> <li>• <b>Frequency:</b> L1-1575 MHz</li> <li>• <b>Position accuracy:</b> &lt;2.5m CEP autonomous &lt;2.0m CEP SBAX</li> <li>• <b>Time to first fix:</b> <ul style="list-style-type: none"> <li>- Hot start: &lt;1s</li> <li>- Warm start: &lt;32s</li> <li>- Cold: &lt;35s</li> </ul> </li> </ul>	<b>GSM</b> <ul style="list-style-type: none"> <li>• <b>Frequency Range(MHz):</b> support 4-frequency 850/900/1800/1900</li> <li>• <b>Channel spacing (Hz):</b> 200</li> <li>• <b>GPRS connectivity:</b> GPRS multi-slot class 10</li> <li>• <b>GPRS mobile station class B</b></li> <li>• <b>SIM card interface:</b> 3.4~4.5V</li> <li>• <b>SMS Storage Capacity:</b> 40 in ME</li> <li>• <b>Internal memory:</b> 3000 log internal memory</li> </ul>
<b>Electrical</b> <ul style="list-style-type: none"> <li>• <b>DC Supply Voltage:</b> 12V or 24V</li> <li>• <b>DC Tolerance Voltage:</b> 9V-32V</li> <li>• <b>Current (GPRS online):</b> 60mA</li> <li>• <b>Current (GPRS transmission):</b> 80mA</li> <li>• <b>Current (Peak):</b> 120mA</li> <li>• <b>Internal battery</b></li> </ul>	<b>Temperature</b> <ul style="list-style-type: none"> <li>• <b>Operating:</b> -20° ~ 55°C</li> </ul> <b>Certification</b> <ul style="list-style-type: none"> <li>• CE, FCC, ROHS</li> </ul> <b>Dimensions</b> <ul style="list-style-type: none"> <li>• 83mm (l) x 74mm (w) x 22 mm (h)</li> <li>• 120mm (w) with external antennas connected</li> </ul>