



PRODUCT CODE: NRW-35K

BARCODE: 9332820005028

PRODUCT DESCRIPTION

Wireless Car Kit with 3.5" LCD colour monitor, 1x CCD Camera & 1x CMOS Camera

NARRATIVE

The NRW-35K features a 3.5" LCD screen that simply plugs into the cig socket. It has a built in receiver for a clear distortion free image from 1 or 2 cameras. Kits come with either CMOS butterfly camera or plug and play commercial grade CCD camera. Easy installation as only needs power. Range is approx. 40 m.

SPECIFICATIONS

NSM-356W:

3.5" LCD Colour Monitor	Display: Colour TFT-LCD
Dot Pitch: 0.073 (H) * 0.219(V)	Resolution: 960(H) * 234(V)
Viewing Angle: U:50/D:55, R/L:60	Brightness: 430cd/m2 Max
Contrast: 300:1	Audio Output: ≤1W
Loudspeaker: ø2.8cm, 16Ω/1W	Power Supply: DC11~32V
Built-in CDS Sensor for Auto Illuminating	Built-in 2.4GHz 4ch receiver
Monitor automatically activated on Detecting Wireless Signal.	If features an On-Screen Menu for all settings; Normal/Mirror View, Reversing Image Delay, Automatic Switch On.
Auto Switch On	Built- in speaker
Dimension: W110x H77 x T25 (mm)	Weight: 250g

CMS-801W:

1/3" CMOS Colour Camera Butterfly mount. Wireless transmission.	Total Pixels: PAL:500 (H) * 582(V), NTSC: 510(H)*492(V)
TV System: NTSC/PAL	Horizontal Resolution: 330 TV Lines
Usable Illumination: 1 Lux (F:2.0)	Sync System: Internal Synchronization
Number of pixels: NTSC:510(H) x 492(V); PAL: 500(H) x 582(V)	Frequency: 2.414GHZ/ 2.432GHZ/ 2.450GHZ/ 2.468 GHZ
Power Supply: 12~24VDC	Weight: 280g

CCD-4105W:

1/3" CCD Colour Wireless cig plug input	Total Pixels: PAL:500 (H) * 582(V), NTSC: 510(H)*492(V)
TV System: NTSC/PAL	Lens Mount: 2.8mm
Horizontal Resolution: 330 TV Lines	Sync System: Internal Synchronization
Number of pixels: NTSC:510(H) x 492(V); PAL: 500(H) x 582(V)	Usable Illumination: 0Lux At Night (18IR LED ON)
IR Power On: CDS Auto Control, Under 10 Lux by CDS(≤10 Lux CDS ON)	IR Distance/Lens Mount: 15M/2.8mm
S/N Ratio: ≥ 48dB (AGC Off)	Video Output: 1.0Vp-p75 ohm
Unobstructed Effective Range: 50 meter	Frequency: ISM 2,400-2,483 MHZ 4CH*
Transmission Power: 10mW/CE; 2mW/FCC	Operating Temperature: -20°C~ +50°C RH95% Max
Power Supply: 11~32VDC	Dimension: 84 x 76 x 70 (mm)

DATE OF PRODUCT RELEASE: April 2012

NRW-35Min *Screen plus CMOS Butterfly mount camera.* RRP \$249 incl
 NRW-35HD *Screen plus CCD Commercial camera.* RRP \$299 incl
 NRW-352K *Screen plus CMOS and CCD cameras.* RRP \$349 incl